



Type: DDTS-145				Part No. DDTS145110 ...		
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
DDTS145110.080	800	800	1120	100	150	---
DDTS145110.085	850	850	1080	100	175	---
DDTS145110.090	900	900	1040	100	200	---
DDTS145110.095	950	950	1000	100	225	---
DDTS145110.100	1000	1000	960	100	250	---
DDTS145110.105	1050	1050	940	100	275	---
DDTS145110.110	1100	1100	920	100	300	---
DDTS145110.115	1150	1150	890	100	325	---
DDTS145110.120	1200	1200	880	100	350	---
DDTS145110.125	1250	1250	860	100	375	---
DDTS145110.130	1300	1300	840	100	400	---
DDTS145110.135	1350	1350	810	100	425	---
DDTS145110.140	1400	1400	800	100	450	---
DDTS145110.145	1450	1450	780	100	475	---
DDTS145110.150	1500	1500	760	100	500	---
DDTS145110.155	1550	1550	730	100	525	---
DDTS145110.160	1600	1600	720	100	550	---
DDTS145110.165	1650	1650	700	100	575	---
DDTS145110.170	1700	1700	680	100	600	---
DDTS145110.175	1750	1750	650	100	625	---
DDTS145110.180	1800	1800	640	100	650	---
DDTS145110.185	1850	1850	620	100	675	---
DDTS145110.190	1900	1900	600	100	700	---
DDTS145110.195	1950	1950	570	100	725	---
DDTS145110.200	2000	2000	560	100	750	---
DDTS145110.205	2050	2050	530	100	775	---
DDTS145110.210	2100	2100	520	100	800	---
DDTS145110.215	2150	2150	500	100	825	---
DDTS145110.220	2200	2200	480	100	850	---
DDTS145110.225	2250	2250	440	100	875	---
DDTS145110.230	2300	2300	400	100	900	---
DDTS145110.235	2350	2350	360	100	925	---
DDTS145110.240	2400	2400	320	100	950	---
DDTS145110.245	2450	2450	280	100	975	---
DDTS145110.250	2500	2500	240	100	1000	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam



WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!

Options:

Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.