



Type: DDTs-150				Part No. DDTs150110 ...		
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
DDTS150110.080	800	800	1150	100	150	---
DDTS150110.085	850	850	1100	100	175	---
DDTS150110.090	900	900	1070	100	200	---
DDTS150110.095	950	950	1030	100	225	---
DDTS150110.100	1000	1000	990	100	250	---
DDTS150110.105	1050	1050	970	100	275	---
DDTS150110.110	1100	1100	950	100	300	---
DDTS150110.115	1150	1150	920	100	325	---
DDTS150110.120	1200	1200	900	100	350	---
DDTS150110.125	1250	1250	890	100	375	---
DDTS150110.130	1300	1300	870	100	400	---
DDTS150110.135	1350	1350	840	100	425	---
DDTS150110.140	1400	1400	810	100	450	---
DDTS150110.145	1450	1450	800	100	475	---
DDTS150110.150	1500	1500	780	100	500	---
DDTS150110.155	1550	1550	760	100	525	---
DDTS150110.160	1600	1600	750	100	550	---
DDTS150110.165	1650	1650	730	100	575	---
DDTS150110.170	1700	1700	700	100	600	---
DDTS150110.175	1750	1750	680	100	625	---
DDTS150110.180	1800	1800	670	100	650	---
DDTS150110.185	1850	1850	650	100	675	---
DDTS150110.190	1900	1900	630	100	700	---
DDTS150110.195	1950	1950	600	100	725	---
DDTS150110.200	2000	2000	590	100	750	---
DDTS150110.205	2050	2050	560	100	775	---
DDTS150110.210	2100	2100	550	100	800	---
DDTS150110.215	2150	2150	530	100	825	---
DDTS150110.220	2200	2200	510	100	850	---
DDTS150110.225	2250	2250	470	100	875	---
DDTS150110.230	2300	2300	430	100	900	---
DDTS150110.235	2350	2350	390	100	925	---
DDTS150110.240	2400	2400	350	100	950	---
DDTS150110.245	2450	2450	310	100	975	---
DDTS150110.250	2500	2500	270	100	1000	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam



WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!

Options:

Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.