



Type: DDTS-40			Part No. DDTS4048 ...			
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
DDTS4048.020	200	400	200	50	---	---
DDTS4048.025	250	500	195	50	---	50
DDTS4048.030	300	600	190	50	---	100
DDTS4048.035	350	700	185	50	---	150
DDTS4048.040	400	800	180	50	---	200
DDTS4048.045	450	900	175	50	---	250
DDTS4048.050	500	1000	170	50	---	300
DDTS4048.055	550	1100	165	50	150	---
DDTS4048.060	600	1200	160	50	175	---
DDTS4048.065	650	1300	155	50	200	---
DDTS4048.070	700	1400	150	50	225	---
DDTS4048.075	750	1500	145	50	250	---
DDTS4048.080	800	1600	140	50	275	---
DDTS4048.085	850	1700	135	50	300	---
DDTS4048.090	900	1800	130	50	325	---
DDTS4048.095	950	1900	125	50	350	---
DDTS4048.100	1000	2000	115	50	375	---
DDTS4048.105	1050	2100	105	50	400	---
DDTS4048.110	1100	2200	95	50	425	---
DDTS4048.115	1150	2300	85	50	450	---
DDTS4048.120	1200	2400	80	50	475	---

\* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam



WE RECOMMEND USE ON THE MAJOR AXIS  
DO NOT DISMANTLE THE SLIDE!!!

**Options:**

Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.