



Type: DDTS-50			Part No. DDTS5060 ...			
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
DDTS5060.020	200	200	310	50	---	---
DDTS5060.025	250	250	305	50	---	50
DDTS5060.030	300	300	300	50	---	100
DDTS5060.035	350	350	290	50	---	150
DDTS5060.040	400	400	280	50	---	200
DDTS5060.045	450	450	270	50	---	250
DDTS5060.050	500	500	260	50	---	300
DDTS5060.055	550	550	250	50	150	---
DDTS5060.060	600	600	245	50	175	---
DDTS5060.065	650	650	240	50	200	---
DDTS5060.070	700	700	230	50	225	---
DDTS5060.075	750	750	220	50	250	---
DDTS5060.080	800	800	210	50	275	---
DDTS5060.085	850	850	200	50	300	---
DDTS5060.090	900	900	195	50	325	---
DDTS5060.095	950	950	190	50	350	---
DDTS5060.100	1000	1000	180	50	375	---
DDTS5060.105	1050	1050	170	50	400	---
DDTS5060.110	1100	1100	165	50	425	---
DDTS5060.115	1150	1150	160	50	450	---
DDTS5060.120	1200	1200	155	50	475	---
DDTS5060.125	1250	1250	150	50	500	---
DDTS5060.130	1300	1300	145	50	525	---
DDTS5060.135	1350	1350	140	50	550	---
DDTS5060.140	1400	1400	135	50	575	---
DDTS5060.145	1450	1450	130	50	600	---
DDTS5060.150	1500	1500	125	50	625	---
DDTS5060.155	1550	1550	120	50	650	---
DDTS5060.160	1600	1600	110	50	675	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam



WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!

Options:

Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.