



Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
DDTS7064.040	400	400	370	50	---	200
DDTS7064.045	450	450	365	50	---	250
DDTS7064.050	500	500	360	50	---	300
DDTS7064.055	550	550	350	50	---	350
DDTS7064.060	600	600	340	50	---	400
DDTS7064.065	650	650	330	50	200	---
DDTS7064.070	700	700	320	50	225	---
DDTS7064.075	750	750	315	50	250	---
DDTS7064.080	800	800	310	50	275	---
DDTS7064.085	850	850	300	50	300	---
DDTS7064.090	900	900	295	50	325	---
DDTS7064.095	950	950	285	50	350	---
DDTS7064.100	1000	1000	280	50	375	---
DDTS7064.105	1050	1050	270	50	400	---
DDTS7064.110	1100	1100	260	50	425	---
DDTS7064.115	1150	1150	255	50	450	---
DDTS7064.120	1200	1200	245	50	475	---
DDTS7064.125	1250	1250	240	50	500	---
DDTS7064.130	1300	1300	230	50	525	---
DDTS7064.135	1350	1350	220	50	550	---
DDTS7064.140	1400	1400	210	50	575	---
DDTS7064.145	1450	1450	200	50	600	---
DDTS7064.150	1500	1500	195	50	625	---
DDTS7064.155	1550	1550	190	50	650	---
DDTS7064.160	1600	1600	180	50	675	---
DDTS7064.165	1650	1650	175	50	700	---
DDTS7064.170	1700	1700	165	100	650	---
DDTS7064.175	1750	1750	160	100	675	---
DDTS7064.180	1800	1800	150	100	700	---
DDTS7064.185	1850	1850	140	100	725	---
DDTS7064.190	1900	1900	135	100	750	---
DDTS7064.195	1950	1950	125	100	775	---
DDTS7064.200	2000	2000	120	100	800	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam



WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!

Options:

Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.