



Type: DDTS-90				Part No. DDTS9072 ...		
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
DDTS9072.060	600	600	720	50	---	400
DDTS9072.065	650	650	680	50	200	---
DDTS9072.070	700	700	640	50	225	---
DDTS9072.075	750	750	620	50	250	---
DDTS9072.080	800	800	600	50	275	---
DDTS9072.085	850	850	565	50	300	---
DDTS9072.090	900	900	550	50	325	---
DDTS9072.095	950	950	540	50	350	---
DDTS9072.100	1000	1000	520	50	375	---
DDTS9072.105	1050	1050	495	50	400	---
DDTS9072.110	1100	1100	470	50	425	---
DDTS9072.115	1150	1150	455	50	450	---
DDTS9072.120	1200	1200	440	50	475	---
DDTS9072.125	1250	1250	415	50	500	---
DDTS9072.130	1300	1300	400	50	525	---
DDTS9072.135	1350	1350	380	50	550	---
DDTS9072.140	1400	1400	360	50	575	---
DDTS9072.145	1450	1450	350	50	600	---
DDTS9072.150	1500	1500	330	50	625	---
DDTS9072.155	1550	1550	310	50	650	---
DDTS9072.160	1600	1600	295	50	675	---
DDTS9072.165	1650	1650	280	50	700	---
DDTS9072.170	1700	1700	270	100	650	---
DDTS9072.175	1750	1750	260	100	675	---
DDTS9072.180	1800	1800	255	100	700	---
DDTS9072.185	1850	1850	240	100	725	---
DDTS9072.190	1900	1900	230	100	750	---
DDTS9072.195	1950	1950	215	100	775	---
DDTS9072.200	2000	2000	200	100	800	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam



WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!

Options:

Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.