



Type: DTS-90				Part No. DTS9036 ...		
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
DTS9036.060	600	600	900	50	---	400
DTS9036.065	650	650	850	50	200	---
DTS9036.070	700	700	800	50	225	---
DTS9036.075	750	750	780	50	250	---
DTS9036.080	800	800	750	50	275	---
DTS9036.085	850	850	710	50	300	---
DTS9036.090	900	900	690	50	325	---
DTS9036.095	950	950	670	50	350	---
DTS9036.100	1000	1000	650	50	375	---
DTS9036.105	1050	1050	620	50	400	---
DTS9036.110	1100	1100	590	50	425	---
DTS9036.115	1150	1150	570	50	450	---
DTS9036.120	1200	1200	550	50	475	---
DTS9036.125	1250	1250	520	50	500	---
DTS9036.130	1300	1300	500	50	525	---
DTS9036.135	1350	1350	480	50	550	---
DTS9036.140	1400	1400	460	50	575	---
DTS9036.145	1450	1450	440	50	600	---
DTS9036.150	1500	1500	420	50	625	---
DTS9036.155	1550	1550	390	50	650	---
DTS9036.160	1600	1600	370	50	675	---
DTS9036.165	1650	1650	350	50	700	---
DTS9036.170	1700	1700	340	100	650	---
DTS9036.175	1750	1750	330	100	675	---
DTS9036.180	1800	1800	320	100	700	---
DTS9036.185	1850	1850	300	100	725	---
DTS9036.190	1900	1900	290	100	750	---
DTS9036.195	1950	1950	270	100	775	---
DTS9036.200	2000	2000	250	100	800	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam



WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!

Options:

Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.