



Type: OWS-40			Part No. OWS4016 ...			
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
OWS4016.030	300	150	250	50	---	100
OWS4016.035	350	175	245	50	---	150
OWS4016.040	400	200	240	50	---	200
OWS4016.045	450	225	235	50	---	250
OWS4016.050	500	250	230	50	---	300
OWS4016.055	550	275	225	50	150	---
OWS4016.060	600	300	220	50	175	---
OWS4016.065	650	325	210	50	200	---
OWS4016.070	700	350	205	50	225	---
OWS4016.075	750	375	200	50	250	---
OWS4016.080	800	400	195	50	275	---
OWS4016.085	850	425	190	50	300	---
OWS4016.090	900	450	180	50	325	---
OWS4016.095	950	475	170	50	350	---
OWS4016.100	1000	500	160	50	375	---
OWS4016.105	1050	525	150	50	400	---
OWS4016.110	1100	550	140	50	425	---
OWS4016.115	1150	575	130	50	450	---
OWS4016.120	1200	600	120	50	475	---
OWS4016.125	1250	625	110	50	500	---
OWS4016.130	1300	650	100	50	525	---
OWS4016.135	1350	675	90	50	550	---
OWS4016.140	1400	700	80	50	575	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam



WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!

Options:

Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.