



Type: TSR-70			Part No. TSR7024 ...			
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
TSR7024.030	300	250	280	50	---	100
TSR7024.035	350	300	275	50	---	150
TSR7024.040	400	350	270	50	---	200
TSR7024.045	450	400	265	50	---	250
TSR7024.050	500	450	260	50	---	300
TSR7024.055	550	500	255	50	150	---
TSR7024.060	600	550	250	50	175	---
TSR7024.065	650	600	245	50	200	---
TSR7024.070	700	650	240	50	225	---
TSR7024.075	750	700	235	50	250	---
TSR7024.080	800	750	230	50	275	---
TSR7024.085	850	800	225	50	300	---
TSR7024.090	900	850	220	50	325	---
TSR7024.095	950	900	210	50	350	---
TSR7024.100	1000	950	200	50	375	---
TSR7024.105	1050	1000	190	50	400	---
TSR7024.110	1100	1050	180	50	425	---
TSR7024.115	1150	1100	170	50	450	---
TSR7024.120	1200	1150	160	50	475	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam



WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!

Options:

Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.