


Type: TSRT-70			Part No. TSRT7024 ...			
Part No.	Installation Length L (mm)	Extension Length D (mm)	* Load per pair (kg)	DRILLING TABLE		
				Dimension A	Dimension B	Dimension C
TSRT7024.030	300	550	280	50	---	100
TSRT7024.035	350	650	275	50	---	150
TSRT7024.040	400	750	270	50	---	200
TSRT7024.045	450	850	265	50	---	250
TSRT7024.050	500	950	260	50	---	300
TSRT7024.055	550	1050	255	50	150	---
TSRT7024.060	600	1150	250	50	175	---
TSRT7024.065	650	1250	245	50	200	---
TSRT7024.070	700	1350	240	50	225	---
TSRT7024.075	750	1450	235	50	250	---
TSRT7024.080	800	1550	230	50	275	---
TSRT7024.085	850	1650	225	50	300	---
TSRT7024.090	900	1750	220	50	325	---
TSRT7024.095	950	1850	210	50	350	---
TSRT7024.100	1000	1950	200	50	375	---
TSRT7024.105	1050	2050	190	50	400	---
TSRT7024.110	1100	2150	180	50	425	---
TSRT7024.115	1150	2250	170	50	450	---
TSRT7024.120	1200	2350	160	50	475	---

* The maximum safe load is given for a fully extended pair of slides, mounted on the major axis, with a load spread uniformly along the inner beam

 WE RECOMMEND USE ON THE MAJOR AXIS
DO NOT DISMANTLE THE SLIDE!!!

Options:
Various dimensions of the main profile, optional slide lengths, extensions, drillings, diameters and hole centers to customer's requirement.